

RUG  
UNDERLAY

kinnasand

This non-skid, lightweight rug underlay is made from a polyester fleece with an acrylic-based adhesive. It is suitable for application on parquet and laminate, cork and PVC flooring as well as ceramic tiles.

The underlay creates a good, solid base for any rug, emphasising its natural beauty and comfort. It is suitable for domestic and commercial use.

#### TECHNICAL FEATURES

- Lightweight and easy to install
- Levels out any small irregularities in the floor
- Leaves no residue
- Extends the lifetime and preserves the original appearance of the rug
- 100% recyclable and produced using environmentally friendly methods
- Suitable for use in combination with heated floors
- Material: 100% polyester fleece with latex treatment (acrylic-based adhesive)
- Height: 3,0 mm
- Weight: 240 g/m<sup>2</sup>

#### INSTALLATION

Install the underlay with the black side up underneath the rug, resized to be 50 mm smaller than the back of the rug.

Make sure that the floor is completely dry and free of grease, stone dust and dust. Do not install the underlay on a recently coated floor. To prevent any chemical reactions between the underlay and any coating, we advise waiting at least three months until after the coating has been applied.

#### MAINTENANCE

Use only professional cleaning products suitable for your floor and not the usual household cleaning products. These can damage the protection layer or lacquer and carry a risk of discoloration. Applying a new polish or other kinds of protective coating may also create bonding problems.

To prevent the underlay from sticking to the floor, we advise ventilating it from time to time. Use this opportunity to clean the floor with a damp cloth. The rug underlay is sensitive to direct sunlight. This may cause it to dry out. Hand wash at 30 degrees. Do not machine-wash, spin or wring out to dry. Do not tumble-dry or iron.